# Air Space

# Student Handout



## Introduction

Heating and cooling costs are one of many problems facing South Dakotans. The harsh South Dakota winters and scorching summers always have been problematic for South Dakotans. Especially now, when fuel costs are reaching all time highs, comfort is giving way to thermostat adjustments. Wars, hurricanes, increased human demand, and damaged pipelines are just a few of the obstacles fueling the energy crisis. Billions of dollars are being invested into alternative fuels and technological advancements to help eliminate the energy crisis in the future. Government incentives like low interest loans or grants to help defer the cost of re-insulating older homes would be an immediate fix to alleviate a portion of the energy demand.

According to the 2nd Law of Thermodynamics, heat will naturally transfer from a warmer body to a colder body. For example: heat will transfer from the inside of a warm house in the winter to the outside. Insulation is designed to prevent the flow of heat though the walls of a house. Insulation has an R-value, which indicates its ability to reduce the amount of heat that passes through it. A higher R-value means more resistance so less heat will pass through. Newer building codes suggest an R-value of 22 in the walls, 11 in the basement and an R value of 44 in the ceiling/roof.

In older homes the insulation was applied loose between the studs. The insulation and the air trapped in the insulation prevented heat from transferring though the walls. Over time, the insulation in older homes has settled to the bottom of the walls. The settling has left large gaps of un-insulated air in most of the wall. The open air space does not insulate very well.

In today's lab, you will test whether a properly insulated home will reduce the amount of heat that is transferred through the walls. Simple materials like cardboard boxes and shredded paper will be used to complete the experiment.

## Materials

(listed per lab group)

- 3 5"x5"x5" cardboard boxes (small boxes all should be same size)
- 3 7"x7"x7" cardboard boxes (small boxes all should be same size)
- 1 Bag of shredded paper or packing peanuts
- 1 Stopwatch or clock with second/minute hands
- 1 Access to an electric balance
- 1 Metric ruler (mark 1/4 line on box)
- 1 Marker (mark 1/4 line on box)
- 3 Indoor/outdoor thermometer (insert probe into the box before it is placed in the freezer)
- 1 Role of masking tape
- 1 Graph paper or access to a computer with graphing program
- 1 Data book to record results
- 1 Freezer

### Process:

A cardboard box (7"x7"x7") will represent a one room house with 4 exterior walls, a floor and a ceiling. A smaller box (5"x5"x5") will be placed in the larger box to represent the interior wall; the space between the boxes represents the space between the interior wall and the exterior of the house.

No insulation will be placed in the space for the 1st setup. The second setup will have insulation on the bottom about 1/4 of the way up the side walls. This will represent an older home with settled insulation. The last setup will be completely insulated. This will be our control because we naturally assume a home should be insulated.

The probe of an indoor/outdoor thermometer will be placed in each of the smaller boxes. The boxes are then placed in a freezer. An initial temperature reading is taken and temperature readings are taken every 2 minutes for 20 minutes and recorded on the data chart.

### Air Space Student Handout

## Setup:

- 1. Obtain the materials listed above.
- 2. Assemble the following:

#### A. Non-insulated home

- Suspend an indoor/outdoor thermometer bulb from the inside of the small box using tape. (Care should be taken so the thermometer bulb is not touched during the assembly.)
- 2. Close the small box secure with tape
- 3. Place the small box inside the larger box
- 4. Close the larger box secure with tape
- Label the box and place to the side (empty box).

#### B. Older home (1/4 insulation)

1. Suspend an indoor/outdoor thermometer bulb from the inside of the small box using tape. (Care should be taken so the thermometer bulb is not touched during the assembly.)

10

- 2. Close the small box secure with tape
- 3. Use a ruler and marker to indicated the 1/4 mark on the side of the large box. The mark should be made on inside and outside of the box. This will be the height of the insulation. The mark should be made 4.5 cm from the bottom of the box.
- 4. Use a balance to measure 35 grams of shredded paper.
- 5. Place approximately 2 cm of shredded paper on the bottom of the large box. Place the small box inside the larger box. Insert the remaining insulation around the smaller box. Fill and compress to the 1/4 line.
- 6. Close the larger box secure with tape
- 7. Label the box and place to the side (Older home 1/4 insulation).

#### C. Insulated home (control)

- 1. Suspend an indoor/outdoor thermometer bulb from the inside of the small box using tape. (Care should be taken so the thermometer bulb is not touched during the assembly.)
- 2. Close the small box secure with tape
- 3. Use a balance to measure 135 grams of shredded paper.
- 4. Place approximately 2.5 cm of shredded paper on the bottom of the large box. Place the small box inside the larger box. Insert the remaining insulation around and on top of the smaller box.
- 5. Close the larger box secure with tape
- 6. Label the box (Insulated home).
- 3. Place the boxes in the freezer. The thermometer readouts should be placed on the top of the freezer. The freezer should not be opened until all of the measurements have been taken.
- 4. An initial temperature reading is taken and temperature readings are taken every 2 minutes for 20 minutes and recorded. (Data Table #1)
- 5. Clean your testing area in accordance to your teacher's discretion.
- 6. Graph the results using an X-Y graph. Time is the independent variable. The independent variable is independent of change and is not affected by the experiment. The independent variable is usually placed on the X-axis. The temperature change is the dependent variable because it changes with time and it is affected by the amount of insulation added to each box. The dependent variable is usually placed on the Y-axis.

Data Table #1			
Time	Non-Insulated	1/4 Insulated	Insulated
(2min)	0 – Grams	Grams	Grams
Initial			
1			
2			
3			
4			
5			
6			
7			
8			
9			

## Air Space Student Handout

# Data analysis (Questions)

	hy must care be taken not to touch the thermometer bulb during the initial setup?
2. W	hy should the freezer remain closed during the investigation?
	hat does R-value mean?
a b	/hat was the decrease in temperature for each of the following?  Loss = (Initial Temp – Final Temp)  1. Non-insulated (°F)  2. 1/4 insulated (°F)  3. Insulated (°F)  Are your results exactly the same as other lab groups?  Can you provide an explanation for your results?
d	. Normally the Celsius scale is used in scientific experiments. Why was the Fahrenheit scale used in this eriment?
	ould re-insulating an older home be an effective method to reduce the amount of energy needed to a home?
1.V 2.a 3.C	the house — extension questions  What is the average monthly bill paid to heat your home? \$

Kids' Quest "Investigators on the Job" is funded in part by SciGirls which is made possible by a grant from the National Science Foundation.









